

Description:

Pendant Light - Interior / Exterior

Applications:

Tree Lighting, Arbors, Cabanas, Pergolas, Gazebos,
Residential/Commercial

Codification:

FF Pendant Light

Fixture Lengths

- 8** 8 in.
- 12** 12 in.
- 18** 18 in.
- 24** 24 in.
- 30** 30 in.

Material

- C** Natural Copper
- S** Stainless Steel (Contact KFi for price and availability)
- P** Powder Coated Steel (Contact KFi for price and availability)

Lamp

- I** 8.0 watt DC Base Incandescent
- L4** 0.4 watt DC Base LED
 - 23 2300 (K) Kelvin
- L9** 0.9 watt DC Base LED
 - 30 3000 (K)
 - 50 5000 (K)

Optional Prewiring

18-2 Cord

- N** None
- 10** 10 ft.
- 20** 20 ft.
- 30** 30 ft.
- 40** 40 ft.
- 50** 50 ft.

Voltage:

12 Volt AC
Requires LV Transformer

Notes:


Firefly pendant lights suspend from the low voltage cord that powers the fixtures. The cord must be 18 AWG 2/C PVC/NYLON TYPE TC DIRECT BURIAL, SUNLIGHT RESISTANT 600V.

Attention:

The above listed "TC" (Tray Cable) MUST BE ROUND in order to function properly with rubber grommet/seal/strain relief.

Notes Regarding Transformers:

When using incandescent lamps (origin of the magic behind Firefly) we welcome voltage drop. This is the reason we offer multi-volt (8, 10, 12 volt) transformers, to extend lamp life. In many cases they can outlast LED lamps.



Available Transformers:

- T-50-S 50 Watt 12 Volt
 - T-100-S 100 Watt 12 Volt
 - T-175-M 175 Watt Multi-volt 8/10/12 Taps
 - T-300-M 300 Watt Multi-volt 8/10/12 Taps
- Enclosures are Stainless Steel Outdoor Rated
*Below Grade Enclosures are Available

Order Specification	$\frac{\text{FF}}{\text{FIXTURE}} - \frac{24}{\text{LENGTH}} - \frac{\text{C}}{\text{MATERIAL}} - \frac{\text{N}}{\text{CORD LENGTH}} - \frac{8}{\text{LAMP}}$
---------------------	--

PROJECT:	FIREFLY BY KFi 3 E. FABRA LN., BOERNE, TEXAS 78006 210 828 7645 WEB: WWW.FIREFLYPENDANTLIGHT.COM Email: www.fireflybykfi@gmail.com
APPROVED:	
NOTE:	
TYPE:	
SPECIFIED	